

	Model : 12M55G2550/5	Date : 21/08/19
	PowerKit Engine Datasheet	Page : 1 / 4

Ratings

RPM	Gross Engine Output	
	PRP kWm	ESP kWm
1500	1985	2210

Basic data

Engine model12M55G2550/5
N° of Cylinders / Valves12 / 48
Cylinders arrangementAt Vee
Bore x Stroke (mm)180 x 215
Displacement (L)65.65
Thermodynamic CycleDiesel 4 stroke
Cooling SystemLiquid (water + 50% antifreeze)
Injection SystemDirect
Fuel SystemHigh Pressure Common Rail
AspirationTurbocharged and Aftercooled
Compression ratio16.5 : 1
Flywheel housingSAE 00
Flywheel21"
N° of teeth on flywheel ring gear202
Inertia of flywheel (kg/m ²)20.78
Inertia of crankshaft (kg/m ²)16.16
Emission standardN/A
Overall Dimensions without radiator (Length x Width x Height) (mm)2934 x 1544 x 2654
Engine dry weight without radiator and without radiator pipes (kg)9550
Engine dry weight with radiator and radiator pipes (kg)TBA
Engine wet weight with radiator (includes oil, coolant) (kg)TBA

	Model : 12M55G2550/5	Date : 21/08/19
	PowerKit Engine Datasheet	Page : 2 / 4

Air intake system

Air intake temperature rise (°C)	≤ 5
Air intake restriction clean filter (mBar)	≤ 30
Air intake restriction dirty filter (mBar)	≤ 70
Recommended air flow @ PRP (m³/min)	132.3
Recommended air flow @ ESP (m³/min)	147.1
Min. diameter of intake pipe (mm)	250

Aftercooling system

Aftercooler system type	Air to Water
Aftercooler heat dissipating capacity @ PRP (kJ/s)	399
Aftercooler heat dissipating capacity @ ESP (kJ/s)	510
Max. intake temperature @ 25°C ambient temperature (°C)	55
Max. difference between intake temperature and ambient temperature (°C)	TBA
Max. intake pressure drop of aftercooler (mBar)	50

Lubrication system

Oil capacity Low / High (L)	380 / 480
Oil pressure in normal condition idle speed (Bar)	≥ 2
Oil pressure in normal condition at 1500 Rpm @ PRP (Bar)	4 - 5.5
Lowest oil pressure alarm (shutdown) (Bar)	2
Max. oil temperature (°C)	105
Oil flow (L/min)	≥ 1300
Oil fuel consumption ratio based on engine fuel consumption data	≤ 0.25 %
Total system capacity (including filters) (L)	560

Heat balance test data (with ambient temperature 28 °C)

Total heat dissipation @ ESP (kJ/s)	4900
---	------

Exhaust system

Max. exhaust back pressure (mBar)	75
Max. exhaust temperature before turbocharger (°C)	≤ 650
Max. exhaust temperature after turbocharger (°C)	TBA
Exhaust flow @ PRP (m³/min)	389.5
Exhaust flow @ ESP (m³/min)	440.8
Min. diameter of exhaust pipe (mm)	280
Max. bending moment of exhaust gas exit flange (Nm)	TBA

 MOTEURS Baudouin	Model : 12M55G2550/5	Date : 21/08/19
	PowerKit Engine Datasheet	Page : 3 / 4

Cooling system without radiator

System designed for ambient temperature up to (°C) ¹	50
Radiator type	Electrical
Fan type Electric driven pusher - 4 x 30 kWe 400 Vac 1450 Rpm motors	
Min. inside diameter of coolant outlet pipe (mm)	96
Coolant capacity of radiator and pipes (L)	TBA
Coolant alarm (shutdown) temperature (°C)	103
Thermostat opening temperature / full open temperature (°C)	78 / 90
Min. pressure in cooling system (Bar)	TBA
Coolant capacity of the engine (L)	306
Cooling fan airflow (m ³ /min)	TBA
Max additional restriction - Duct allowance (Pa)	TBA

Fuel system

Governor	ECU
Max. restriction at fuel pump inlet (Bar)	0.1
Max. fuel return restriction (Bar)	0.2
Max. fuel inlet temperature (°C)	70
Fuel supply flow (L/hr)	2800
Min. pressure of fuel pump (Bar)	0.5
Min. diameter of inlet pipe (mm)	25
Min. diameter of return pipe (mm)	25

Electrical system

Electrical system voltage (negative to ground) (Vdc)	24
Starter power (kW)	2 x 8.5
Battery charger current (A)	55
Battery charger absorbed power (kW)	1.6
Max. electric resistance of starting circuit (Ω)	0.008
Min. sectional area of wire (mm ²)	2 x 95
Min. cold start temperature without auxiliary starting device (°C) ²	-10
Min. cold start temperature with auxiliary starting device (°C) ²	TBA

¹ The indicated value is for an engine tested at 100% PRP, in an open condition, without an enclosure or container, without any airflow obstruction in the front of the radiator, with free exhaust gas exit and with the engine thermostatic valve in its full open condition, without a closing plate present.

² Engines used in emergency standby application or application that require immediate start under load, must be equipped with coolant heaters. Baudouin recommend heaters installation to be executed by providing constant coolant circulation across all the engine components. Two heaters are required for V-type engines, one per each side.

 MOTEURS Baudouin	Model : 12M55G2550/5	Date : 21/08/19
	PowerKit Engine Datasheet	Page : 4 / 4

Performance data

Mean Piston Speed (m/s)	10.75
BMEP (Bar)	26.9
Fan absorbed power (kW)	TBA

Noise

Diesel engine noise (Acoustic power level) (dB(A))	123.8
Noise - upper side (dB(A))	107
Noise - right side (view from flywheel) (dB(A))	106,2
Noise - left side (view from flywheel) (dB(A))	106,3
Noise – front (radiator) side (dB(A))	106,2
Noise – rear (flywheel) side (dB(A))	105,4

Notes :

- a) Noise test made at 100% of the ESP power, 1 mt. distance, on engine without radiator, without cooling fan and without silencer.
- b) Noise test refers to GB/T 1859 norm : Reciprocating internal combustion engines. Measurement of emitted airborne noise. Engineering method and survey method

Fuel consumption

Rating	gr/kWh	L/hr
100% ESP	187.8	494,1
100% PRP	185	437,2
75% PRP	186.5	330,5
50% PRP	196.3	231,9
25% PRP	209.9	124
Fuel consumption tolerance + 3 %		

Ratings definitions

Emergency Standby Power (ESP)

Emergency Standby Power is the maximum power available for a varying load for the duration of a main power network failure. The average load factor over 24 hours of operation should not exceed 70% of the engine's ESP power rating. Typical operational hours of the engine is 200 hours per year, with a maximum usage of 500 hours per year. This includes an annual maximum of 25 hours per year at the ESP power rating. No overload capability is allowed. The engine is not to be used for sustained utility paralleling applications.

Prime Power (PRP)

Prime Power is the maximum power available for unlimited hours of usage in a variable load application. The average load factor should not exceed 70% of the engine's PRP power rating during any 24 hour period. An overload capability of 10% is available, however, this is limited to 1 hour within every 12 hour period.

- 1) All ratings are based on operating conditions under ISO 8528-1, ISO 3046, DIN6271. Performance tolerance of ±5%.
- 2) Test conditions : 100 kPa, 25°C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L. Derating may be required for conditions outside these; please contact the factory for details.
- 3) Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.